

# Single Arm Operator

## Winder

INTERLOCK™

ASSA ABLOY



The Single Arm Operator conveniently controls awning or casement windows fitted with 2-bar stays or butt hinges or awning windows fitted with projected 4-bar stays. The Single Arm Operator controls the opening sash by means of the connecting arm and a sliding track. Where positive seal compression is required, use of a window fastener is recommended.

### Features:

- Easy to install with a minimum of routing required
- Supplied with a 350mm long face fixing track
- A smooth and quiet nine-turn operator
- The control handle has a unique pivoting action that allows the handle to be folded flat in a parked position at any sash open angle
- New Zealand made

### Options:

- Available in left-hand or right-hand options
- Available in a wide range of powdercoat colours



### Specifications:

Application	Min. Height	Min. Width	Max. Height	Max. Width
Awning	600mm	600mm	N/A	900mm
Casement 2-Bar Stay	***	450mm	***	600mm
Casement Butt Hinge	N/A	400mm	***	750mm

\* Note: A sash height to width ratio may apply, check stay specifications.

No.	Description
1	GARDEN OPERATOR 250mm
2	CASE OP PIVOTING HANDLE
3	CASE OP S'HOLE INST
4	CASE OP BASE PACKER
5	GARDEN OP TRACK 350mm

